



## BARRIER GLOSS

### DESCRIPTION:

Concrete Chemistries Barrier Gloss is a highly durable, chemical and stain resistant urethane sealer designed for use on interior and exterior surfaces. Barrier's water-based formula is easy to apply and becomes extremely strong once cured. This durable coating will not cloud or yellow when exposed to UV rays and highly resistant to the harsh effects of outdoor weathering. Barrier is an excellent choice for commercial applications that endure significant foot traffic.

\* Satin Gloss finish.

### USES:

Use on concrete, masonry, pavers, terrazzo, Saltillo, terra cotta, and many other architectural surfaces.

### COVERAGE:

Approximately 200 to 500 sq. ft. per gallon.

### APPLICATION:

1. Ensure surface is clean, dry and free of waxes or coatings.
2. Avoid applying during the hottest part of the day. Do not apply when temperatures are over 90 or below 50°F.
3. Apply sealer with a microfiber mop, natural fiber brush, paint pad applicator or low pressure sprayer. Distribute product evenly over entire surface to ensure uniform coverage. \*Note: For an even cure avoid puddling. Multiple thin coats are better than one thick coat.
4. Allow at least 30 minutes drying time between applications. Product may dry quicker during outdoor application.
5. After final coat, allow to dry for 6 hours prior to surface traffic. Full cure is achieved within 48-72 hours. Do not mop or saturate with water for the first 7 days.
6. Clean tools with water